

Video Conferencing for Small Meeting Rooms

Lifesize® Icon 400™

SYSTEM COMPONENTS

- Lifesize Icon 400 with embedded PTZ camera
- Lifesize Phone HD, Phone 2nd Generation, or Digital MicPod
- Power supply/cables
- Lifesize Remote Control

COMMUNICATIONS

- SIP, H.323, 128 Kbps–6.0 Mbps
- 1 x RJ-45 Network LAN 10/100
- 1 x Lifesize Link for Lifesize Phone HD, Phone 2nd Generation, or Digital MicPod

SUPPORT FOR SINGLE DISPLAY

- Any display with HDMI input supporting 720p or 1080p video modes

1080P30 ZOOM CAMERA

- Wide-angle zoom lens with:
 - Diagonal field of view: 80 degrees
 - Horizontal field of view: 70 degrees
 - Vertical field of view: 39 degrees
- 3x optical zoom, 2x digital zoom, 5x total
- Auto focus/automatic gain control
- 10 camera presets (near or far end)

VIDEO SPECIFICATIONS

- Maximum resolution 1920x1080, 16:9 aspect ratio¹
- All resolutions progressive scanning
- Over 200 resolutions supported
- Example bitrates and resolutions (H.264 High Profile, AAC-LD):
 - 600 Kbps (720p30)
 - 820 Kbps (720p60)
 - 1.2 Mbps (1080p30)

VIDEO STANDARDS

- H.264 High Profile, H.264 Baseline Profile, H.263+, H.263

VIDEO INPUTS (1 INPUT)

- 1 x HD Video In (up to 1080p30) HDMI enabled

VIDEO OUTPUTS (1 OUTPUT)

- 1 x HD Video Out (up to 1080p30) HDMI enabled

FULLY INTEGRATED, HD AUDIO

LIFESIZE PHONE HD/DIGITAL MICPOD

- 90 Hz up to 22 kHz
- Audio pickup range up to 4.57 m (15 ft)
- 48kHz audio sampling
- Powered by Icon 400 directly through Lifesize Link cable
- Support for one Lifesize Phone HD, Phone 2nd Generation, or Digital MicPod
- Ships with 4 m cable (Digital MicPod) or 9 m cable (Lifesize Phone HD or Phone 2nd Generation)
- Optional 15 m cable available

AUDIO FEATURES

- WebRTC NetEQ packet loss concealment
- Full duplex for natural conversations
- Echo cancellation for echo-free calls
- Automatic gain control
- Automatic noise reduction

AUDIO STANDARDS

- G.711, G.722, G.722.1 and G.722.1C licensed from Polycom®, MPEG-4 AAC-LC, MPEG-4 AAC-LD, Opus

AUDIO INPUTS (2 INPUTS)

- 1 x Lifesize Link (Lifesize Phone HD, Phone 2nd Generation, or Digital MicPod)
- 1 x HD Video In

AUDIO OUTPUTS (2 OUTPUTS)

- 1 x Lifesize Link (Lifesize Phone HD or Phone 2nd Generation)
- 1 x HD Video Out

OTHER SUPPORTED STANDARDS

- H.221, H.224, H.225, H.231, H.239/BFCP, H.241, H.242, H.245, H.281, RFC 3261, RFC 3264, RFC 2190, RFC 3407, RFC 2833

USER INTERFACE & FEATURES

- Simplified user interface
- Heads up remote control
- Seamless call escalation to a group call
- Graphical user interface administration console
- Multiple languages supported
- Do Not Disturb mode
- Video mute
- Picture-in-picture

LIFESIZE CLOUD-BASED SERVICE²

- Seamless call escalation for video and voice participants
- Calendar, meeting directory, favorites, unified searchable directory
- Automatic provisioning
- Guest calling
- Single button recording and sharing
- Mobile calling
- Video network management
- Secure firewall traversal, plus NAT
- Automatic software updates

SECURITY

- Ability to disable HTTP, SSH services
- H.235 (AES) encryption support including strict compliance (non-AES version available)
- TLS/SRTP support
- Kensington Security Slot

NETWORKING FEATURES

- Adaptive motion control (AMC) including forward error correction (FEC) for superior video quality in all network conditions
- NAT/firewall traversal (H.460/SIP)
- Auto bandwidth detection
- IPv4 support

DIRECTORY AND ADDRESS BOOK

- Up to 10,000 directory entries
- Global search tool
- LDAP support/H.350 compliant
- Calendar/meeting directory support
- H.323 URI dialing support (Annex O)

SYSTEM MANAGEMENT

- Web interface
- Auto configuration
- SNMP
- Backup and restore capability
- 1 x USB 2.0
- Serial support

POWER

- AC voltage 100–240V, 50–60 Hz, 2.31A via external 19VDC power supply

ENVIRONMENTAL DATA

- Operating temperature: 0°C (32°F) to 40°C (104°F)
- Operating humidity: 15% to 85%, noncondensing
- Storage temperature: –20°C (–4°F) to 60°C (140°F)
- Storage humidity: 10% to 90%, noncondensing

VIDEO DEVICE DIMENSIONS

- Width: 216.5 mm (8.52")
- Depth: 119.4 mm (4.70")
- Height: 125.4 mm (4.94")
- Weight: 1.04 Kg (2.29 lbs)

MOUNTING OPTIONS

- Mounting holes: 2 x M5 screw holes 150 mm (6 in) apart
- Mounting screws: 2 x M5 screws (Max insertion depth: 3.8 mm)

REGULATORY NUMBER

- Lifesize Icon 400 = LFZ-033

¹ When paired to the Lifesize cloud-based service, some features and settings are managed by Lifesize to tailor the user experience for use with the service.

² Requires a Lifesize subscription. Feature availability and price vary by subscription plan, selected options, and paired devices.

HEADQUARTERS

Austin, Texas, USA
+1 512 347 9300
Toll Free US +1 877 543 3749

EMEA REGIONAL OFFICE

London
+44 207 5962 835

APAC REGIONAL OFFICE

Singapore
+65 6631 2831



www.lifesize.com
E-mail: info@lifesize.com



© 2019 Lifesize, Inc. All rights reserved. Information contained in this document is subject to change without notice. Lifesize and the Lifesize logo are registered trademarks of Lifesize, Inc. All other trademarks are the property of their respective owners.

DS_Icon400_US_0119